



SILA-COVER 300 INSTRUCTIONS FOR USE

Thank you for choosing Sila-Cover 300 as a protective cover for your silage clamp. To ensure long and effective life please follow the guide lines below..

Note. In the majority of cases Sila-Cover 300 is supplied in lengths to match the width of the clamp with extra length to accommodate over fill and provide “tuck in”. The Sila-Bags should be filled to 60% with clean pea gravel, allowing the bag to flex and be most effective. **DO NOT USE SAND OR SHARP OBJECTS.**

- 1 Before placing Sila-Cover 300 in position, the silage should be heaped in the middle of the clamp with the polythene sheets in position creating a good seal.
- 2 Sila-Cover 300 should be placed with the loops facing upwards.
- 3 Start at the back of the silage clamp, working forward overlapping 50cm at each join. (Fig 1)
- 4 Place Sila-Bags in a continuous run around all outer edges and over joins, ensuring the Sila-Cover is taut in each direction.
- 5 Place additional intermediate Sila-Bags as required.
- 6 Sila-Bags placed on the sloping sections can be secured to the loops using the plastic hooks provided (10 supplied with every 50 bags) to prevent slipping
- 7 When feeding silage, Sila-Cover 300 can be folded back for access and afterwards returned to protect against birds.
- 8 Individual covers should be folded and stored immediately upon removal from the silage clamp.

Following these practical guidelines will ensure many seasons use.

